

## Saxon - Bug #4457

### MessageListener.message() terminate parameter set incorrectly

2020-02-11 00:47 - Michael Kay

|                                 |             |                                      |            |
|---------------------------------|-------------|--------------------------------------|------------|
| <b>Status:</b>                  | Closed      | <b>Start date:</b>                   | 2020-02-10 |
| <b>Priority:</b>                | Normal      | <b>Due date:</b>                     |            |
| <b>Assignee:</b>                | Michael Kay | <b>% Done:</b>                       | 100%       |
| <b>Category:</b>                | s9api API   | <b>Estimated time:</b>               | 0:00 hour  |
| <b>Sprint/Milestone:</b>        |             | <b>Spent time:</b>                   | 0:00 hour  |
| <b>Legacy ID:</b>               |             | <b>Fixed in Maintenance Release:</b> | 9.9.1.7    |
| <b>Applies to branch:</b>       | 9.9, trunk  | <b>Platforms:</b>                    |            |
| <b>Fix Committed on Branch:</b> | 9.9, trunk  |                                      |            |

**Description**

(Since 9.9.1.6) A call to a user-supplied MessageListener.message() method does not set the terminate parameter to true when <xsl:message terminate="yes"> was specified.

Unit test TestMessageListener.testMessageTerminate() created.

#### History

##### #1 - 2020-02-28 12:02 - Michael Kay

- Status changed from New to Resolved
- Fix Committed on Branch 9.9, trunk added

A slightly messy fix, but it works: the xsl:message code now inserts into the pipeline (between the document builder and the message emitter) a custom ProxyReceiver that adds the TERMINATE property to the startDocument() event.

##### #2 - 2020-03-05 11:09 - O'Neil Delpratt

- Status changed from Resolved to Closed
- % Done changed from 0 to 100
- Fixed in Maintenance Release 9.9.1.7 added

Patch applied in the 9.9.1.7 maintenance release.