

Saxon - Bug #4796

Provide a way to obtain an empty XdmSequenceliterator

2020-10-17 10:47 - Michael Kay

| | |
|---|---|
| Status: Closed | Start date: 2020-10-17 |
| Priority: Normal | Due date: |
| Assignee: Michael Kay | % Done: 100% |
| Category: s9api API | Estimated time: 0:00 hour |
| Sprint/Milestone: | Spent time: 0:00 hour |
| Legacy ID: | Fixed in Maintenance Release: 10.3 |
| Applies to branch: 10, trunk | Platforms: |
| Fix Committed on Branch: 10, trunk | |

Description

Chapman Flack points out on the saxon-help mailing list that there is no easy way to obtain an empty XdmSequenceliterator.

A simple solution to this is to change the declaration of XdmValue.iterate() -- it always returns an XdmSequenceliterator, so we might as well declare it as such.

History

#1 - 2020-10-17 10:59 - Michael Kay

- Status changed from New to Resolved
- Applies to branch 10, trunk added
- Fix Committed on Branch 10, trunk added

I have implemented this change on the 10.x and 11.x branches

#2 - 2020-10-28 18:58 - O'Neil Delpratt

Bug fix applied in the Saxon 10.3 maintenance release

#3 - 2020-10-28 19:13 - O'Neil Delpratt

- Status changed from Resolved to Closed
- % Done changed from 0 to 100
- Fixed in Maintenance Release 10.3 added